

20.1" 1U KEYBOARD DISPLAY DESIGNED FOR ALL INDUSTRIAL APPLICATIONS

- RESOLUTION 1600 X 1200
- 300 NIT UXGA DISPLAY
- USB/PS2 KEYBOARD WITH MOUSE PAD
- WIDE VIEWING ANGLE
- 0 TO 50°C OPERATION
- 2 POINT LOCK WHEN DISPLAY IS DOWN
- 19" RACK COMPATIBLE



Specifications	
Display Type:	20.1" TFT
Active Display Area:	16.06" (w) x 12.05" (h) 408 mm x 306.1 mm
Pixel Pitch:	.255 mm
Brightness:	300 nits
Viewing Angle:	Left/Right 80°/80° Up/Down 80°/80°
Contrast Ratio:	800:1
Response Time:	Tr=4 ms; Tf=1 ms
Display Colors:	16.7M
Input Signal:	Video: Analog 0.7V p-p/75 Ω Sync: Separate H&V
Video Input Connectors:	HD-15
Video Inputs:	VGA-VXGA (HD-15)
Video Cable:	Integrated HD15 with Keyboard and Mouse Functions
Resolutions Supported:	640 x 480 800 x 600 1024 x 768 1280 x 1024 1600 x 1200
Native Resolution:	1600 x 1200 (UXGA)
Full Keyboard Options:	PS2/USB Keyboard with Mouse Pad

Environmental	
Temperature:	Operating: 0°C to 50°C Storage: -20°C to 65°C
Humidity (Non- Condensing):	Operating: 10 to 80% Storage: 5 to 95%
Altitude:	Operating: 0 to 10,000 ft. Storage: 0 to 40,000 ft.
Power Requirements:	Voltage: 115/220 VAC @ 50/60 Hz Internal Power: 50W Current: .5a
Dimensions & Weight:	Height: 1.73" (44 mm) Width: 17.4" (442 mm) Depth: 25.59" (650mm) Weight: 44 lbs (20 kg)
Agency:	UL, CE
Optional KVM:	8 Port

Aydin Displays is:



6/1/10

AYDIN DISPLAYS

1 RIGA LANE BIRDSBORO PA 19508 USA

PHONE: 610-404-7400 FAX: 610-404-8190

TOLL FREE: 866-367-2934

WWW.AYDINDISPLAYS.COM

All specifications subject to change without notice.
For additional information, please contact your Aydin Displays sales representative.

Your partner in
display technology